

THE **Q** HIGHLIGHTS THE QUALICO ADVANTAGE. THESE ARE ITEMS THAT QUALICO KNOWS ARE IMPORTANT AND FEELS YOU DESERVE IN YOUR NEW FORT McMURRAY HOME.

## FOUNDATION SPECIFICATIONS

### FOUNDATION WALLS

- 8" thick "Ultra Vertical" 20mpa air entrained concrete mix
- Reinforced with 10m rebar grid
- 8' basement ceiling
- Asphalt emulsion damp proofing applied to below grade portion of house walls
- Perforated "Big O" weeping tile complete with high grade ¾" washed rock
- Sump pit complete with sump pump and discharge

### BASEMENT FLOOR

- 4" thick 20mpa concrete mix on 40mm crushed rock base 8" deep
- Steel trowel finish

**Q** • Painted grey with approved concrete paint

## FRAMING SPECIFICATIONS

### FLOOR

- Engineered Truss Joist system with 23/32" T+G OSB glued and screwed floor sheathing
- Housed stringer, closed rise stairs

### ROOF

- Engineered Roof Trusses and components, 7/16" OSB roof sheathing

### WALLS

**Q** • 9' main floor ceilings

- 2" x 6" spruce exterior walls sheeted with 3/8" osb and placed 2' on centre
- 2" x 4" spruce interior walls placed 16" on centre or as per plan

**Q** • Full width 2" x 8" rear deck nailer

## BUILDING ENVELOPE SPECIFICATIONS

### ROOF

- Q** • **IKO Cambridge 30 year Architectural asphalt shingles c/w drip edge to match metal color**
- Shingles laid over 15lb felt paper
  - Valleys, plumbing stacks, roof vents, and eaves protected with IKO Ice and Water Shield membrane

### WINDOWS AND DOORS

- Titan and Carriage Series by All Weather Windows

**Q** • **Double Glazed Argon filled Low E windows**

- PVC window frames and jambs c/w screens and handles
- Insulated Fiberglass Entry Doors with metal clad wooden jambs

### EXTERIOR WALLS

- Vinyl siding as per plan
- Aluminum soffit and fascia as per plan
- Decorative trim and cladding as per plan
- Aluminum eavestroughs and down spouts

**Q** • **Exterior Envelope complete with building paper, galvanized flashing; all joints/penetrations sealed with peel and stick membrane**

- R-20 friction fit fiberglass batts
- Low expansion Spray Foam around all windows, doors, and penetrations
- 6mil poly vapor barrier
- Poly hats on all exterior receptacles
- ½" drywall (moisture resistant in tub/shower locations)

### ATTIC/CEILING

**Q** • **R-60 attic insulation (R-20 fiberglass batts plus R-40 blown in cellulose insulation)**

- Low expansion Spray Foam around all penetrations
- 6mil poly vapor barrier
- ½" CD drywall
- Insulated, sealed attic hatch

### BASEMENT

- Full height frost walls with R-12 friction fit fiberglass batts
- 6mil poly vapor barrier

## MECHANICAL SPECIFICATIONS

### PLUMBING

- 3 piece Basement Bathroom rough in
- 2 Frost Free Hose Bibs as per plan
- Laundry connections
- Dishwasher connection
- Kohler Sterling toilets with easy clean seats in white finish
- Kohler Sanibel china bathroom basins in white finish c/w Kohler Coralais Single Lever Chrome faucets
- Hytec fiberglass Tub/Showers in white finish c/w Kohler Coralais Single Lever Chrome valve.

**Q** • **On Demand Hot Water System**

- Double Stainless Steel Kitchen Sink
- Kohler Forte Brushed Nickel Kitchen Faucet c/w Vegetable Spray

**Q** • **Central Vacuum System rough-in**

### HEATING AND VENTILATION

- American Standard 95% Efficient Natural Gas Forced Air Furnace
- General Air Fan Assisted Humidifier

**Q** • **Central Exhaust Bathroom Fan System interlocked with furnace**

**Q** • **Programmable Thermostat**

- Main floor Humidistat
- Bath fan rough in to future basement bathroom
- Dryer vent to exterior
- Over the range micro hood vent to exterior
- White finish on all floor registers and cold air returns

**Q** • **All duct work Power Vacuumed before possession**

### ELECTRICAL

- 100 amp service
- Copper wiring
- Smoke and Carbon Monoxide detectors as per code
- 2 Exterior Weather Resistant GFCI receptacles on individual circuits
- CAT5 prewired to all bedrooms, kitchen, living room,
- Coaxial cable prewired to all bedrooms, living room
- 220 v. Range connection
- 220 v. Dryer connection
- Recessed lighting as per plan
- White Decora style switches and receptacles
- Builder's light fixture package with pewter finish

**Q** • **High Efficiency Mini Fluorescent bulbs**

- Front door chime

## INTERIOR SPECIFICATIONS

### PAINT AND STAIN

- One prime coat and 2 finish coats of high quality interior paint
- Doors, trim, mantles, and plant shelves sprayed trim color

**Q** • **Railings stained to match cabinet color**

- Knock down ceiling texture

(continued on back)

## MILLWORK

- Stained and lacquered maple railing, shoe, and posts complete with wrought iron balusters
- Painted mdf colonial style casing and base board complete with plinth blocks and architrave top molding
- Plant shelves as per plan
- Painted mdf shelving
- Painted Carmelle doors with painted mdf jambs
- Bi-folds on all closets
- Hemlock wall mounted hand rail to basement

## HARDWARE

- Weiser Galiano lever style handles – privacy on master bedroom and all bathrooms
- Weiser front handle and lock set on front door
- Other exterior doors have Weiser Galiano handles with deadbolts keyed alike
- Mirrors in all bathrooms
- Pewter spring and hinge stops
- Taymor Azure pewter toilet paper holders
- Taymor Azure pewter towel bars
- Pewter house numbers

## CABINETS

- Cabinets with full 5/8" backs and real maple veneer

### Q • Solid maple doors

- Quick release European style hinges

### Q • Solid drawer fronts

- Solid maple crown molding
- Beveled edge kitchen tops complete with Tile Back Splash
- Ultra Select Vanity tops with rolled edges

## FLOORING

### Q • Mercier ¾" Canadian made Hardwood Flooring installed as per predetermined floor layout

- Natural Shield 36oz Canadian made carpet with 7lb under padding installed as per predetermined floor layout

### Q • Ceramic Tile flooring (various brands) laid over ½" plywood glued and screwed as per predetermined floor layout

## APPLIANCES

- Frigidaire Professional Series Stainless Steel OTR Microwave
- Frigidaire Professional Series Stainless Steel DishWasher
- Frigidaire Stainless Steel Series Self Cleaning Range
- Frigidaire Stainless Steel Series Frost Free Refrigerator
- Inglis Top loading washer and front loading Dryer

## EXTERIOR SPECIFICATIONS

### PARKING & SIDEWALK

- 3' wide Sidewalk from curb to front landing, 4" thick 28mpa Artivia **Exposed Aggregate** Sidewalk, air entrained concrete mix on 40/20mm road crush base
- Reinforced by 2' x 2' 10m rebar grid
- Double gravel Parking Pad at lane
- **Exposed aggregate precast front stairs** placed on wing walls extending to footing depth

### EXTERIOR FEATURES

- Aluminum handrails as required
- Front landscaping as per architectural requirements

### GENERAL CONDITIONS

- Specifications subject to change without notice or obligation
- Variations of these specifications may occur due to the unique characteristics of individual plans, building lots or Architectural Controls
- Errors and omissions allowed

Witness \_\_\_\_\_

\_\_\_\_\_  
Purchaser(s) \_\_\_\_\_

\_\_\_\_\_  
Qualico Developments West Ltd.

\_\_\_\_\_  
Date

The Developer reserves the right to make modifications and changes to the information contained herein. Renderings, photos and sketches are representational and may not be accurate. Dimensions, sizes, specifications, layout and materials are approximations only and are subject to change without notice. E.&O.E.

Last Updated May 2011

